

Cold Header Die Repair Press

DOCUMENT 12033



500 ton CHDR



- Alloy steel bed cover plate
- 12-18" stroke available
- Two hand control with combination pushbutton and joystick
- Work shelf for die loading
- Down-acting ram with adjustable tonnage
- Kevlar rod guard anti-shrapnel
- Fast advance/slow pressing speeds
- Self-contained hydraulics
- 480v, 3ph with lockable disconnect
- Easy access sliding door with interlock
- 18-24-30" daylight openings available
- Lexan safety viewing window
- Led interior worklight



Three (3) solid steel sides and sliding safety door access with ballistics-rated Lexan viewing window to prevent shrapnel injuries while pressing brittle carbide inserts.

SAVAGE HYDRAULIC PRESSES ARE APPLICATION-SPECIFIC AND JOB-ENGINEERED
Tonnage, bed size, stroke, daylight openings, and speeds are all customer-selected to meet your exact specifications.



SAVAGE ENGINEERING & SALES, INC.
4855 Chaincraft Road
Garfield Heights, OH 44125

• Phone: 216-587-2885 • Fax: 216-587-0613 • www.savagepress.com • sales@savagepress.com •

metal forming

compression molding

straightening

sheet molding

drawing

assembly

horizontal

compaction

powder compaction

laminating

gluing/bonding

forcing

die repair

blanking

die spotting

special work

composites molding

bulldozing

trimming

hot press

fluid forming

hobbing

automation